



TEX PUMPS

PERFORMANCE DATA FOR SUBMERSIBLE PUMP SET SINGLE PHASE 220V / 50 HZ

IS : 8034



CML 6749290

TYPE	KW/HP	STAGE	PIPE SIZE mm	DISCHARGE IN LITRES PER HOUR								
				1000	1500	2000	2500	3000	3500	3800	4000	4500
TSR-75/08	0.55/0.75	8	32	40	37	35	31	28	24	20	17	13
TSR-75/10	0.55/0.75	10	32	50	44	38	33	29	24	22	19	16
TSR-75/12	0.55/0.75	12	32	60	52	39	28	16	6	-	-	-
TSR-100/7	0.75/1.0	7	32	55	51	47	43	39	35	30	12	-
TSR-100/10	0.75/1.0	10	32	58	53	49	45	36	28	17	9	-
TSR-100/12	0.75/1.0	12	32	60	56	47	40	37	32	28	24	20
TSR-100/14	0.75/1.0	14	32	70	63	56	51	42	30	10	-	-
TSR-100/18	0.75/1.0	18	32	80	72	64	49	32	16	5	-	-
TSR-150/9	1.1/1.5	9	32	60	55	52	47	43	35	25	15	-
TSR-150/12	1.1/1.5	12	32	75	68	63	58	52	45	25	10	-
TSR-150/15	1.1/1.5	15	32	82	74	69	66	57	48	35	-	-
TSR-150/18	1.1/1.5	18	32	90	82	76	70	66	61	58	56	49
TSR-150/24	1.1/1.5	24	32	108	93	82	66	36	19	8	-	-
TSR-200/12	1.5/2.0	12	32	72	65	60	58	54	49	45	40	35
TSR-200/15	1.5/2.0	15	32	80	70	66	63	60	57	53	49	43
TSR-200/24	1.5/2.0	24	32	125	105	98	95	76	65	40	15	-
TSR-200/30	1.5/2.0	30	32	140	110	83	70	53	31	18	7	-